

kli-nit[®] CT-2


Electrical Contact Cleaner



Be 100% Sure

PROPERTIES

Appearance..... Colorless liquid
Density.....About 1.0 g/cc (of base)
Shelf life3Years
CFC..... Does not contain
Solid contents.....0.015%
Drying time.....10-15seconds
Specific Gravity (20°C).....0.89+0.02
Dielectric strength
(ASTM D877)..... 31.500V
Expected coverage60-100 m²/l



CT-2 is used by:

- Electricity boards,
- Railways,
- Thermal power plants,
- Nuclear power plants
- Oil Refineries, Fertilizer Plants,
- Defence - Air force stations, Ordnance factories,
- Steel Plants
- Telephone Exchanges, etc

Protect. Prevent. Maintain. Power failure

- **OIL FREE** - contact cleaner , Evaporates completely . No residue
- **PREVENT** - electrical equipment failures due to dirty contacts , oxidation , carbon deposits , moisture , grease , corrosion
- **AVOIDS** pollution flashover
- **REDUCES** contamination level & surface treatment
- **RESTORES** resistances values and electrical properties
- **REMOVES** dust , grime , bird dropping from the Insulator stains , Insulator burns , greases & foreign particles
- **REMOVES OXIDATION** of copper/silver/aluminium conductors
- **SAFE ON** metal parts , varnish and most plastics
- **PACK SIZE:** 350ml and 500ml



An ISO 9001:2008 Certified Company
Kappa Sigma Corporation

104, Shiv Industrial Estate, Mumbai - 400 012, India

Tel. : +91 22 2372 2888 Fax : 2373 8899 sales@kli-nit.com http://www.kli-nit.com

